

EntryLine Touchscreen



The budget-friendly alternative

With a Full HD screen, the EntryLine offers all the basic features you need. It's a budget-friendly alternative to the Pro Line.

Specifications

| Screen | 55" | 65" | 70" |
|-----------------------|------------------------------------------------------------|------------------------------------------------------------|------------------------------------------------------------|
| Bezel color | Sand blasted aluminium (black) | Sand blasted aluminium (black) | Sand blasted aluminium (black) |
| Diagonal | 55 inch | 65 inch | 70 inch |
| Panel type | Full HD LED | Full HD LED | Full HD LED |
| Maximum Resolution | 1920 x 1080 @ 60Hz | 1920 x 1080 @ 60Hz | 1920 x 1080 @ 60Hz |
| Response Time Panel | 6 ms | 6 ms | 6 ms |
| Glass Plate | Anti-Glare | Anti-Glare | Anti-Glare |
| Glass Thickness | 4 mm / 0.16 inches | 4 mm / 0.16 inches | 4 mm / 0.16 inches |
| Glass Hardness | Mhos 7 | Mhos 7 | Mhos 7 |
| Aspect ratio | 16:9 | 16:9 | 16:9 |
| Contrast ratio | 1400:1 | 1400:1 | 4000:1 |
| Brightness | 350 cd/m2 | 350 cd/m2 | 300 cd/m2 |
| Number of colours | 8 bit (16.7M) | 8 bit (16.7M) | 8 bit (16.7M) |
| Viewing Angle | 178° | 178° | 178° |
| Panel Refresh Rate | 120Hz | 120Hz | 120Hz |
| Modules | | | |
| PC module slot | Yes | Yes | Yes |
| Touch module | | | |
| Touch module | Entry Line 55" HD | Entry Line 65" HD | Entry Line 70" HD |
| Type | IR-pro | IR-pro | IR-pro |
| Multi-touch | Yes (10 points) | Yes (10 points) | Yes (10 points) |
| Multi writing | Yes (5 points) | Yes (5 points) | Yes (5 points) |
| Auto-calibration | Yes | Yes | Yes |
| Resistant to sunlight | Yes | Yes | Yes |
| Supported OS | Windows 7, 8.1 & 10/Mac OS/ Linux/Android and Chrome OS | Windows 7, 8.1 & 10/Mac OS/ Linux/Android and Chrome OS | Windows 7, 8.1 & 10/Mac OS/Linux/ Android and Chrome OS |

| Audio | 55" | 65" | 70" |
|--------------|---------------------|---------------------|---------------------|
| Speakers | Stereo (2 speakers) | Stereo (2 speakers) | Stereo (2 speakers) |
| Power | 2 x 10 Watt / 8Ω | 2 x 10 Watt / 8Ω | 2 x 10 Watt / 8Ω |
| Microphone | N/A | N/A | N/A |

| Special features | 55" | 65" | 70" |
|----------------------------|------------------|------------------|------------------|
| ProMenu | Yes, version 2.0 | Yes, version 2.0 | Yes, version 2.0 |
| NFC reader/writer | N/A | N/A | N/A |
| Pen-tray | N/A | N/A | N/A |
| Over the Air Updates (OTA) | Yes | Yes | Yes |

| Connections | 55" | 65" | 70" |
|-----------------------------|--------------------------------------------|--------------------------------------------|--------------------------------------------|
| HDMI 1.4 | 3 (3x 1.4) | 3 (3x 1.4) | 3 (3x 1.4) |
| HDMI 2.0 | N/A | N/A | N/A |
| HDMI Port with MHL | Yes, HDMI 3 | Yes, HDMI 3 | Yes, HDMI 3 |
| VGA + Audio in | 3 | 3 | 3 |
| VGA Passthrough | 1 | 1 | 1 |
| Audio output analog | 3,5 mm Stereo Jack (adjustable) | 3,5 mm Stereo Jack (adjustable) | 3,5 mm Stereo Jack (adjustable) |
| Audio output digital | Coaxial (fixed) | Coaxial (fixed) | Coaxial (fixed) |
| RS232 control | 1 (Sub-D, 9 pins) | 1 (Sub-D, 9 pins) | 1 (Sub-D, 9 pins) |
| AV | 1 (including adapter to 3 x RCA connector) | 1 (including adapter to 3 x RCA connector) | 1 (including adapter to 3 x RCA connector) |
| USB Touch port | 1 (USB-B female) | 1 (USB-B female) | 1 (USB-B Female) |
| LAN port for online updates | 1 (RJ-45) | 1 (RJ-45) | 1 (RJ-45) |
| Wi-Fi for online updates | Yes | Yes | Yes |
| Webcam Mount + top USB | N/A | N/A | N/A |

| Environmental conditions | 55" | 65" | 70" |
|---------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Operation Temperature | 0 - 38°C / 32 - 100.4 °F | 0 - 38°C / 32 - 100.4 °F | 0 - 38°C / 32 - 100.4 °F |
| Storage Temperature | -20 - 60°C / -4 - 140 °F | -20 - 60°C / -4 - 140 °F | -20 - 60°C / -4 - 140 °F |
| Storage Humidity | 10% - 90% | 10% - 90% | 10% - 90% |
| Operation Humidity | 10% - 90% | 10% - 90% | 10% - 90% |
| Altitude | < 2000 meter / < 6561.68 feet | < 2000 meter / < 6561.68 feet | < 2000 meter / < 6561.68 feet |

| General Information | 55" | 65" | 70" |
|---------------------------------------------|--------------------------------------------------|----------------------------------------------------|----------------------------------------------------|
| Voltage | ~ 100-240 V (50/60Hz) | ~ 100-240 V (50/60Hz) | ~ 100-240 V (50/60Hz) |
| Power consumption (Without modules) | 156 watt | 200 watt | 208 watt |
| Stand-by power consumption | ≤ 0,5 Watt | ≤ 0,5 watt | ≤ 0,5 watt |
| Gross Weight | 45 kg / 99.21 lbs | 61 kg / 134.48 lbs | 72 kg / 158.73 lbs |
| Netto Weight | 35 kg / 77.16 lbs | 45 kg / 99.21 lbs | 56 kg / 123.46 lbs |
| Dimensions of the screen (W x H x D) | 1302 x 819 x 96 mm / 51.26 x 32.24 x 3.8 inches | 1521 x 943 x 97 mm / 59.88 x 37.13 x 3.82 inches | 1664 x 1034 x 97 mm / 65.51 x 40.71 x 3.82 inches |
| Dimensions of the total packing (W x H x D) | 1458 x 932 x 220 mm / 57.4 x 36.69 x 8.66 inches | 1695 x 1090 x 235 mm / 66.73 x 42.91 x 9.25 inches | 1803 x 1160 x 243 mm / 70.98 x 45.67 x 9.57 inches |
| VESA Standard | VESA 400 x 400 | VESA 600 x 400 | VESA 600 x 400 |
| Certifications | CE/FCC/IC and RCM | CE/FCC/IC and RCM | CE/FCC/IC and RCM |
| Warranty | 5 year | 5 year | 5 year |